



TATA LPT 1623

**ENGINEERED FOR EFFICIENCY,
EXTRA MILES GUARANTEED.**

ENGINE	
Model	Cummins B5.9 E-III
Capacity	6l, 6 Cylinder Turbocharged
Type	Intercooler 158 @ 2,500
Power (kW at r/min)	789 @ 1,550
Torque (Nm at r/min)	
TRANSMISSION	
Model	Eaton
Shift	Manual
No. of gears	6+1
First gear ratio	7.05
Top gear ratio	0.78
DRIVE AXLE	
Reduction type	Single
Final ratio	5.86
CLUTCH	
Type	Single
Diameter (mm)	380
BRAKES	
Type	Full Air S-Cam
Front	Full Air S-Cam
Rear	Full Air S-Cam
Anti-lock braking system (ABS)	Standard

MAJOR DIMENSIONS	
Overall Height (mm)	2,877
Overall Length (mm)	9,047
Overall Width (mm)	2,474
Front Overhang (mm)	1,515
Rear Overhang (mm)	2,340
Wheelbase (mm)	5,195
MASS	
GVM (kg)	16,000
V (kg)	16,000
GCM (kg)	21,400
D/T (kg)	21,400
Permissible body + payload (kg)	10,500
Tare - total (T) (kg)	5,500
Permissible Rear axle weight (kg)	9,000
Permissible Front axle weight (kg)	7,000
Manufacturers Rear axle weight (kg)	9,000
Manufacturers Front axle weight (kg)	7,000
FUEL TANK	
Fuel Tank Capacity (Litre)	350
Tyres	295/80 R22.5-16PR

*Tag axle option also available


							
Dropside	Van Body	Tautliner	Reefer Body	Skip Loader	Truck Tractor	Tipper Truck	Water Tanker



8T Payload



6 cyl, 6l Cummins Engine
with Eaton Transmission



Available in 4x2, 6x2
(with Tag Axle)



5yr/500,000 km
Driveline Warranty



Standard
ABS