



TATA LPT 1518

RUGGEDNESS MEETS RELIABILITY

ENGINE	
Model	Cummins B 180 20 (Euro 2)
Capacity	6l, 6 Cylinder
Type	Turbocharged Intercooler
Power (kW at r/min)	132 @ 2,500
Torque (Nm at r/min)	650 @ 1,500
TRANSMISSION	
Model	G-750
Shift	Manual
No. of gears	6+1
First gear ratio	6.58
Top gear ratio	0.77
DRIVE AXLE	
Reduction type	Single
Final ratio	5.86
CLUTCH	
Type	Single
Diameter (mm)	380
BRAKES	
Type	Full air S-Cam
Front	Drums
Rear	Drums
Anti-lock braking system (ABS)	Standard

MAJOR DIMENSIONS	
Overall Height (mm)	2,800
Overall Length (mm)	9,047
Overall Width (mm)	2,440
Front Overhang (mm)	1,515
Wheelbase (mm)	5,195
MASS	
GVM (kg)	14,900
V (kg)	14,900
GCM (kg)	21,400
D/T (kg)	21,400
Permissible body + payload (kg)	9,500
Tare - total (T) (kg)	5,400
Permissible Rear axle weight (kg)	10,200
Permissible Front axle weight (kg)	6,000
Manufacturers Rear axle weight (kg)	10,200
Manufacturers Front axle weight (kg)	6,000
FUEL TANK	
Fuel Tank Capacity (Litre)	350
TYRES	
Tyres	11 R22.5-16PR

*Also Available in Sleeper Cab



Dropside



Van Body



Tautliner



Reefer Body



Skip Loader



Truck Tractor



Tipper Truck



Water Tanker



8T Payload



Sleeper/ Day Cab



6 cyl,
6l Cummins Engine



Available in 4x2,
6x2 (with Tag Axle)



5yr/500,000 km
Driveline Warranty



Standard
ABS